3 2 1 REVISION HISTORY ZONE REV **APPROVED** DESCRIPTION DATE SCOPE: THIS TECHNICAL DATA BULLETIN EXPLAINS THE TRANSITION FROM THE VERSION 1 TO THE VERSION 2 BOLT AND FIRING PIN FOR THE REVOLUTION (CMR) RIFLE. IT ALSO EXPLAINS THE INTENTIONAL NON-COMPATIBILITY BETWEEN THE 2 SYSTEMS. **INITIAL RELEASE** 12/26/2018 B. KLAR D D BACKGROUND: THE FIRING PIN HEAD IS GROOVED. THIS IDENTIFIES IT AS VERSION 2 THE ONGOING DEVELOPMENT OF THE REVOLUTION PLATFORM HAS RESULTED IN THE NEED TO RECONFIGURE THE BOLT AND THE FIRING PIN. THE BOLT BAND IS GROOVED FOR GAS RINGS. EXPERIMENTATION WITH DIFFERENT CALIBERS, PRIMARILY THIS IDENTIFIES IT AS VERSION 2 THOSE WITH HIGHER PRESSURES, RESULTED IN THE REDUCTION OF THE FIRING PIN TIP DIAMETER. THE REDUCED DIAMETER RESULTS IN LESS SIGNS OF PRIMER FLOW AND AIDS IN ELIMINATING PIERCED PRIMERS. V2 FIRING PIN ALSO. THE ADDITION OF THE DIRECT IMPINGEMENT OPERATING SYSTEM POF-USA SKU 01492 OPTION REQUIRED THE BOLT TO BE MODIFIED BY ADDING GROOVES FOR THE GAS RINGS. PRINCIPALLY, POF-USA BELIEVES IN MAINTAINING A REDUCED AMOUNT OF PART NUMBERS IN ORDER TO ACHIEVE OUR GOALS. SINCE BOTH OF THESE CHANGES BECAME REQUIREMENTS AT AROUND THE SAME TIME, THE DECISION WAS MADE TO IMPLEMENT THEM **VERSION 2** V2 BOLT: POF-USA SKU 01493 TOGETHER BY DESIGNING THE V2 BOLT AND V2 FIRING PIN. V2 BOLT ASSEMBLY: POF-USA SKU 01494 **HOW TO ID** CONSIDERATIONS: 9 THE V2 COMPONENTS ARE NOT COMPATIBLE WITH THE V1 COMPONENTS. THE V1 COMPONENTS ARE NOT COMPATIBLE WITH THE V2 COMPONENTS. THE V2 FIRING PIN WILL NOT FIT INTO A V1 BOLT.
IF THE SMALLER TIPPED V2 FIRING PIN WAS USED IN A V1
BOLT, THE RESULT WOULD BE NON IGNITION OR PIERCED PRIMERS ON MOST, IF NOT ALL AMMUNTION ATTEMPTED TO BE FIRED FROM THE FIREARM. WE HAVE ADDED A SHOULDER TO THE REAR OF THE FIRING PIN TO PREVENT THIS. THIS IS ILLUSTRATED ON SHEET 2 THE V1 FIRING PIN WILL NOT FULLY FIT INTO A V2 BOLT.
THE V1 FIRING PIN TIP DIAMETER WILL NOT PASS THROUGH THE **VERSION** 1 NO GROOVE ON HEAD В В TIGHTER DIAMETER OF THE V2 BOLT. **HOW TO ID** THIS IS ILLUSTRATED ON SHEET 3 COMPONENT UPGRADES AND REPLACEMENT: THE FOLLOWING SERVICE PART SKUS ARE CURRENT AT THE TIME OF THIS DOCUMENT'S RELEASE: NO GROOVE ON BAND 01494 - V2 BOLT ASSEMBLY **NO GAS RINGS** 01492 - V2 FIRING PIN 01493 - V2 BOLT THE FOLLOWING SERVICE PART SKUS HAVE BEEN DISCONTINUED AND SHOULD BE REPLACED WITH THE SKUS ABOVE WHEN NEEDED: 01409 - V1 BOLT ASSEMBLY. (REPLACE WITH V2 BOLT ASSEMBLY) 01411 - V1 FIRING PIN. (REPLACE WITH 01492 V2 FIRING PIN AND 01493 V2 BOLT) CAD GENERATED DRAWING 01408 - V1 BOLT (REPLÀCE WITH 01493 V2 BOLT AND 01492 V2 FIRING PIN) DO NOT MANUALLY UPDATE APPROVALS IF YOU HAVE ANY QUESTIONS, CONTACT POF-USA CUSTOMER SERVICE DATE THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE SOLE PHONE: (623)561-9572 MODELED BY PROPERTY OF PATRIOT ORDNANCE FACTORY, INC. ANY REPRODUCTION PATRIOT ORDNANCE FACTORY 12/17/2018 EMAIL: SALES@POF-USA.COM IN WHOLE OR IN PART WITHOUT THE WRITTEN PERMISSION OF PATRIOT RKIAR DRAWING TITLE ORDNANCE FACTORY IS STRICTLY PROHIBITED DRAWN BY TECHNICAL BULLETIN REVOLUTION / CMR 12/17/2018 B. KLAR THIRD ANGLE PROJECTION THIS DOCUMENT IS SUBJECT TO THE ARMS EXPORT CONTROL ACT (22 ENGINEERING V2 BOLT ASSY & COMPONENTS ----/--/--U.S.C. 7728) AND THE INTERNATIONAL TRAFFIC IN ARMS REGULATIONS (22 C.F.R. PARTS 120-130). A PRIOR
AUTHORIZATION OR LICENSE FROM THE U.S. STATE DEPARTMENT
DIRECTORATE OF DEFENSE TRADE CONTROLS IS REQUIRED TO EXPORT, MANUFACTURING SIZE CAGE CODE DRAWING NUMBER REVITR 100756 В 4Y6X4 QUALITY RE-EXPORT, RETRANSFER OR SHOW THIS DOCUMENT TO ANY FOREIGN PERSON WHETHER IN THE UNITED STATES OR ABROAD. SCALE 1:1 WEIGHT SHEET 1 OF 3 4 2



